

Accessories

Base for scouring work

Order number 369.314



Technical attributes

Diameter in mm	80 Ø
QTY/PKG	1

Tool-free interchangeable protective guard for optimally guiding the machine and effective dust extraction.

Extraction hood

Order number 366.528



Technical attributes

Diameter in mm	115 Ø
QTY/PKG	1

With swivel segment and brush ring for grinding work.

Scouring head complete, pointed

Order number 503.037



Technical attributes

QTY/PKG	1
Dimensions in mm	80 Ø

Complete with 12 pointed hard metall carbide scouring discs. For removing hard plaster, concrete, foam backing and adhesive residues, paint on

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

plaster, epoxy plaster, flexible protective coatings, plaster on wooden beams and latex/oil paints on plaster.

TC scouring discs, pointed

Order number 366.501



12 pointed carbide scouring discs with fixing bolts and guide discs .

Technical attributes

QTY/PKG	1 set
---------	-------

Scouring head complete, flat

Order number 503.045



Fitted with 12 flat hard metall carbide scouring discs. For removing soft materials, including plaster, green concrete, foam backing and adhesive residues, soft PU coatings, paint coatings on plaster, plaster on wooden beams and latex/oil paint on plaster, shuttering protrusions and concrete runs on fresh concreted surfaces. The flat form leaves the surface smooth (pull cutting).


Technical attributes

Dimensions in mm	80 Ø
QTY/PKG	1

Accessories

TC scouring discs, flat

Order number 366.617



12 flat carbide scouring discs with fixing bolts and guide discs.

Technical attributes

QTY/PKG	1 set
---------	-------

Velcro sanding paper PURFLEX



Ideally suited for working wood and metal.


Technical attributes

Dimensions in mm	Grit	QTY/PKG	Order number
115 Ø	P 24	25	381.195
115 Ø	P 40	50	381.209
115 Ø	P 60	50	381.217
115 Ø	P 80	50	381.225
115 Ø	P 100	50	381.233
115 Ø	P 120	50	381.241
115 Ø	P 150	50	381.268
115 Ø	P 180	50	381.276

Accessories

Diamond sanding pad

Order number 386.197



Technical attributes	
Dimensions in mm	115 Ø
Grit	50
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Diamond sanding pad

Order number 386.200



Technical attributes	
Dimensions in mm	115 Ø
Grit	100
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Accessories

Diamond sanding pad

Order number 386.219



Technical attributes	
Dimensions in mm	115 Ø
Grit	200
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Diamond sanding pad

Order number 386.227



Technical attributes	
Dimensions in mm	115 Ø
Grit	400
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Accessories

Diamond sanding pad

Order number 386.235



Technical attributes	
Dimensions in mm	115 Ø
Grit	800
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Diamond sanding pad

Order number 386.243



Technical attributes	
Dimensions in mm	115 Ø
Grit	1500
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Accessories

Diamond sanding pad

Order number 386.251



Technical attributes	
Dimensions in mm	115 Ø
Grit	3000
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Diamond sanding pad

Order number 386.278



Technical attributes	
Dimensions in mm	115 Ø
Grit	10000
QTY/PKG	1

For use with velcro sanding disc 115 Ø. Sanding pads for dry grinding, a great advantage in the repair and renovation areas. Suitable for sanding and polishing granite worktops, fine stoneware tiles, floor tiles, concrete surfaces in the field of vision, natural stone on windowsills, cover panels, sculptures, steps.

Accessories

Concrete-Jet diamond grinding disc

Order number 503.053



Technical attributes

Dimensions in mm	115 Ø
QTY/PKG	1

Diamond grinding disc suitable for grinding concrete parts, roughing old weathered concrete, hard cement plaster, removing shuttering protrusions and concrete runs, hardened epoxy resin coatings and the natural sintering on concrete components. High grinding capacity and service life from the innovative segment design. Optimal ground preparation for further coating.

Screed-Jet diamond grinding disc

Order number 503.061



Technical attributes

Dimensions in mm	115 Ø
QTY/PKG	1

Grinding disc for abrasive materials. For removal of formwork transitions and concrete runs from freshly concreted surfaces, mineral adhesives, screeds, plaster, mortar, abrasive lime sand brick, sandstone, chamotte, asphalt.

Accessories

Surface-Jet diamond grinding disc

Order number 503.096



Technical attributes

Dimensions in mm	115 Ø
QTY/PKG	1

Special grinding disc for cosmetic treatment of concrete and removal of graffiti, as well as for removal of slight unevenness and transitions from concrete parts, soiling on concrete and hard plaster.

PCD grinding disc

Order number 503.118



Technical attributes

Dimensions in mm	115 Ø
QTY/PKG	1

Grinding disc fitted with polycrystalline diamond segments. For the removal of thermally sensitive coatings such as adhesives, sealants, plastic coatings, bitumen coatings from mineral substrates. The PCD segments enable coatings to be removed quickly and effectively without sticking.

Accessories

TC-Jet carbide grinding disc

Order number 503.126



Technical attributes

Dimensions in mm	115 Ø
QTY/PKG	1

Carbide grinding disc equipped with soldered carbide cutters. For grinding soft plaster, removing paint and tile adhesive on soft plaster, grout and fillers, aged fillers and sealants and for sanding tile adhesive on soft plaster.

Turbo-Jet diamond grinding disc

Order number 503.088



Technical attributes

Dimensions in mm	115 Ø
QTY/PKG	1

Turbo-Jet grinding disc with optimum removal rate. The large number of diamond segments provides a considerably quieter operating performance and a more attractive sanding pattern. Ideal for surface grinding on mineral substrates.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Velcro backing pad Ø 115, Bowl

Order number 503.754




Technical attributes

Dimensions in mm	115 Ø
QTY/PKG	1

Backing pad with velcro face Bowl for securing the abrasives with the velcro system. As damping elements 12 mm cellular rubber pads ensure uniform pressure distribution.

Clip adapter

Order number 408.360



Technical attributes

QTY/PKG	1
---------	---

For connecting a FLEX power tool to extraction units from other manufacturers. Suitable for hoses inside Ø 27 mm, outside Ø 36 mm, with auxiliary air adjustment.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Fast clip adapter

Order number 410.497



Technical attributes

QTY/PKG	1
---------	---

Change adapter on electric power tools with closed FLEX clip-system for quick and easy detachment/attachment (quick clamping ring).

Carrying case L-BOXX®

Order number 414.093



Technical attributes

External dimensions L x W x H	442 x 357 x 253 mm
Internal dimensions L x W x H	378 x 306 x 209 mm
Weight	2,8 kg
QTY/PKG	1

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.


FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Anti slip insert L-BOXX®

Order number 419.389




Technical attributes

Size (W x L x H)	378 x 306 x 3 mm
QTY/PKG	1

Soft insert mat made of rubber suitable for the L-BOXX® type 238. Protects the boxx and the material on the floor from damage during transportation.

Case insert

Order number 414.182



Technical attributes

QTY/PKG	1
---------	---

Matching insert for RETECFLEX for carry case L-BOXX® 238.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Trolley L-BOXX®

Order number 419.400



Technical attributes

Dimensions in mm	646 x 492 x 182
Weight	3,8 kg
QTY/PKG	1

Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.