

2600 watt angle grinder T-Rex with enormous reserves of power, 230 mm

L 26-6 230

Order number 436.704



Technical attributes

| | |
|--------------------|--------------------|
| Max. disc diameter | 230 mm |
| No load speed | 6500 rpm |
| Power input | 2600 watt |
| Power output | 1800 watt |
| Tool fixture | M 14 |
| Clamping collar Ø | 64 mm |
| Cable length | 4,0 m |
| Size (W x L x H) | 500 x 106 x 145 mm |
| Weight | 6,35 kg |

Standard equipment

| | |
|---------------------------------|---------|
| 1 guard grinding 230 Ø | 338.729 |
| 1 SoftVib handle | 325.384 |
| 1 clamping flange | 338.753 |
| 1 SDS-Clic quick-clamp nut M 14 | 253.049 |
| 1 hexagon socket wrench, SW 6 | 104.167 |
| 1 pin wrench | 100.110 |

2600 watt angle grinder T-Rex with enormous reserves of power, 230 mm

- + Microprocessor control with soft start, restart protection after power failure, overload protection, CDC-electronic feedback control
- + Anti-Kickback - this shuts down the motor on the disc being blocked
- + Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- + Highly efficient and resilient motor for more power output
- + An additional vibration damping ring between the motor housing and rear handle reduces the vibrations.
- + SoftVib handgrip for reduced vibration can be mounted in three positions.
- + Rear shaft handle with soft padding for secure grip. The grip area turns 90° to the right and left for an optimum working position
- + Spindle lock
- + Removable covering cap for easy change of carbon brushes
- + Tool-free adjustment of safety guard
- + Cutting guard (389.625) or cover for cutting guard (446.068), as an optional accessory

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Diamantjet - diamond cutting disc, standard, concrete

Order number 349.054



Fast, long-life universal cutting disc, suitable for concrete and stone

Technical attributes

| | |
|------------------|--------------|
| Dimensions in mm | 230 Ø x 22,2 |
| QTY/PKG | 1 |

Diamantjet - diamond cutting disc, universal

Order number 500.720



Universal cutting wheel for the most common construction site materials such as concrete B45 (hard concrete), soft granite, clinker and brick.

Technical attributes

| | |
|------------------|--------------|
| Dimensions in mm | 230 Ø x 22,2 |
| QTY/PKG | 1 |

SDS-Clc quick-clamp nut

Order number 253.049



For tool-less disc change suitable for discs from Ø 150-230 mm.

Technical attributes

| | |
|---------|---|
| QTY/PKG | 1 |
|---------|---|

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

SoftVib side handle

Order number 325.384



Technical attributes

| | |
|---------|------|
| Type | M 14 |
| QTY/PKG | 1 |

SoftVib handle with vibration cushioning, significantly reducing the vibration transmitted to hands and arms and moderating the risk of vibration-related injury to the operator.

Sanding guard

Order number 338.729



Technical attributes

| | |
|----------------|-----|
| Diameter in mm | 230 |
| QTY/PKG | 1 |

Sanding guard.

Accessories

Cutting guard

Order number 389.625



Cutting guard, suitable for L 21-6/L 24-6/L 26-6 230.

Technical attributes

| | |
|----------------|-----|
| Diameter in mm | 230 |
| QTY/PKG | 1 |

Extraction hood

Order number 445.487



Extraction hood kit for working with cutting discs for 230 mm angle grinders. Consisting of extractor with guide wheel and aluminium cover. Can be fitted to the existing guard without using any tools.

Technical attributes

| | |
|----------------|-----|
| Diameter in mm | 230 |
| QTY/PKG | 1 |

Accessories

Disc guard cover

Order number 446.068



For tool-free conversion of the existing guard for cutting work.

Technical attributes

| | |
|----------------|-----|
| Diameter in mm | 230 |
| QTY/PKG | 1 |

Extraction hood cutting for large angle grinder, 230 mm

Order number 471.895



Detachable extraction hood with efficient dust extraction for precise cuts when working with diamond cutting wheels in conjunction with 230 mm angle grinders. Extremely stable, the stabiliser element prevents distortion caused by the side weight of the angle grinder. Base plate with rollers for easy feed, the side handle can be fitted on either the left or right. Incl. suction connection for FLEX clip system and adapter for guide rail. Depth stop with scale for presetting the cutting depth for use with or without a guide rail. Maximum cutting depth 60 mm.

Technical attributes

| | |
|------------------|----------------|
| Diameter in mm | 230 |
| Size (W x L x H) | 365x195x290 mm |
| QTY/PKG | 1 |

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Elastic support plate with clamping nut M 14

Order number 124.079



Backing pads for 180 mm fiber grinding discs.

Technical attributes

| | |
|------------------|-------|
| Dimensions in mm | 180 Ø |
| QTY/PKG | 1 |

Carrying case

Order number 444.391



Impact-resistant plastic box with insert for large angle grinders (up to Ø 230), and renovation grinders LD 18-7 125 R / 150 R, LD 24-6 180. Includes holder for handle, disk up to Ø 230 mm and transparent lidded compartment DIN A5.

Technical attributes

| | |
|---------|--------|
| Weight | 4,0 kg |
| QTY/PKG | 1 |