FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com

FLEX

Cordless rotary hammer drill 18,0 V

CHE 2-26 18.0-EC C



Cordless rotary hammer drill 18,0 V

- + Brushless motor with greater efficiency and a longer service life
- + Powerful motor with 2.6 joules of impact energy and a high rate of removal
- + Function switch with four functions: drilling, hammer drilling, chiselling, chisel adjustment + Rotation stop for chiselling
- + Ideal for daily use for drilling and chiselling in concrete, brickwork, timber and metal
- + Drilling chuck can be removed without tools

+ Quick tool change: universal application, with SDS Plus drill chuck or 13 mm quick-release chuck

+ Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency

+ Decoupled, ergonomic handle with rubberised grip surface. Vibrations are reduced by a sprung damper and additional vibration damping between the housing and handle

- + Accelerator switch with lock-on function
- + Robust gearbox housing made of die-cast aluminium
- + Electronic quick-acting brake
- + Non-rotating additional handle with depth stop
- + Integrated LED lamp with persistence function
- + LED battery capacity display

+ FLEX battery system: suitable for FLEX 18,0 V/5,0 Ah battery packs. Delivery does not include battery and charger

Order number 491.314

Technical attributes	
Battery voltage	18 V
Battery capacity	5,0 Ah
No load speed	0-980 rpm
Blows per minute	0-4350 bpm
Single impact energy (EPTA)	2,6 J
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in concrete	26 mm
Max. drill hole Ø in wood	30 mm
Tool fixture	SDS-plus
Chuck Ø	1,5 - 13 mm
Size (W x L x H)	360 x 85 x 230 mm
Weight without battery	3,18 kg

Standard equipment

1 chuck BF SDS-plus CHE2	468.835
1 handle	436.364
1 depth stop	417.769