

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Rotary hammer drill, 2,3 kg, SDS-plus

FHE 2-22 SDS-plus

Order number 413.674



Rotary hammer drill, 2,3 kg, SDS-plus

- + Light-weight and handy 710 watt pistol-shaped fixing hammer
- + Hammer drilling
- + Max.drilling range up to 22 mm in concrete
- + Ideally suited for drilling/hammer drilling, diameter 4-12 mm in concrete for attachment of dowels and anchors
- + Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- + Depth limit gauge: for precision drilling
- + Accelerator switch with lock-on function
- + Robust glass fibre reinforced housing

Technical attributes

No load speed	0-1400 rpm
Blows per minute	0-4300 bpm
Single impact energy (EPTA)	2,1 J
Max. drill hole Ø in concrete	22 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	26 mm
Power input	710 watt
Tool fixture	SDS-plus
Cable length	4,0 m
Size (W x L x H)	345 x 80 x 200 mm
Weight	2,3 kg

Standard equipment

1 handle	416.126
1 drill depth stop	416.118
1 carrying case L-BOXX® 136	414.085
1 case insert	414.042

Accessories

SDS 2-plus drill



Technical attributes

Diameter in mm	Length in mm	QTY/PKG	Order number
4	110	1	367.931
5	110	1	367.958
6	110	1	367.966
5	160	1	367.974
6	160	1	367.982
8	160	1	367.990
10	160	1	368.008
12	160	1	368.016
6	210	1	368.024
8	210	1	368.032
10	210	1	368.040
12	210	1	368.059
14	210	1	368.067
16	210	1	368.075
8	260	1	368.083
10	260	1	368.091
12	260	1	368.105
14	260	1	368.113
16	310	1	368.121
18	200	1	368.148
20	200	1	368.156
18	450	1	368.164
20	450	1	368.172
22	450	1	368.180
25	450	1	368.199

Drill with 2 solid carbide alloy cutters, reinforcement chamfer and centering point for easy, precision-point working. Asymmetrical, high-capacity double conveyor spirals for quick transfer of the drill dust. Core reinforcement for maximum energy transfer from hammer drill to drill tip. Vibration-damping and also conveys more energy to the cutting bit. Ideal for drilling in concrete, masonry and natural stone.

Accessories

Hammer drill bit set SDS-plus

Order number 414.026



Set consisting of 1 x D 5x110, 1 x D 6x110, 1 x D 6x160, 1 x D 8x160, 1 x D 10x160.

Technical attributes

QTY/PKG	1
---------	---

Hammer drill bit set SDS-plus

Order number 414.034



Technical attributes

Diameter in mm	8
Length in mm	250
QTY/PKG	5

Drill bits with 2 main and 2 secondary cutting edges and centring tip for simple, pinpoint drilling even in reinforced concrete. With a 4-spiral drill bit shank for quicker, optimum removal of the drilling dust and to reduce the drill bit temperature.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

SDS-plus adapter

Order number 368.652



Adapter for 1/2" drill chuck (Order No. 272.639).

Technical attributes

QTY/PKG	1
---------	---

SDS-plus M14 adapter

Order number 374.091



M 14 threaded mixer paddle adapter. Useable with SDS-plus hammer drill.

Technical attributes

QTY/PKG	1
---------	---

Drill dust adapter

Order number 394.025



Technical attributes

Dimensions in mm	290 x 65
QTY/PKG	1

The drill dust extractor is connected to the suction hose of the FLEX vacuum cleaners or to different adapters so that the dust is extracted directly through the drill hole. There is no dust residue. For drilling applications up to \varnothing 24 mm.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Carrying case L-BOXX®

Order number 414.085




Technical attributes

External dimensions L x W x H	442 x 357 x 151 mm
Internal dimensions L x W x H	378 x 311 x 107 mm
Weight	2,2 kg
QTY/PKG	1

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.

Case insert

Order number 414.042



Technical attributes

QTY/PKG	1
---------	---

Matching insert for CHE 2-28/FHE 2-22 SDS plus for carry case L-BOXX® 136.

Accessories

Drill dust adapter

Order number 513.776



Technical attributes

QTY/PKG

1

The drill dust extractor has a large vacuum chamber and a soft, flexible rubber seal. As a result, the drill dust adapter sucks itself tightly even onto uneven surfaces, with the powerful air flow capturing the drill dust and conveying it to the vacuum cleaner. The additional brush segment automatically closes the opening even with smaller drill diameters, so that no dust can escape to the outside. There are no dust residues. For drilling work up to drill \varnothing 67 mm. Clip hose connection \varnothing 32 mm.

Grid foam insert L-BOXX®

Order number 419.370



Technical attributes

QTY/PKG

1

Grid foam insert for the L-BOXX® type 136. The perforated foam allows the foam insert to be individually adjusted to the contents.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Accessories

Trolley L-BOXX®

Order number 419.400



Technical attributes

Dimensions in mm	646 x 492 x 182
Weight	3,8 kg
QTY/PKG	1

Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.