

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Roto random orbit polisher

XFE 7-15 150

Order number 418.080



Roto random orbit polisher

- + VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + Free-spinning drive for hologram-free finishing
- + 15 mm orbit for high efficiency
- + Continuous speed control trigger: for a gentle start and a lock-on for continuous operation
- + Cushioned special hook and loop pad for polishing.
- + Counterweight for smoother operation
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints

Technical attributes

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
Orbit	15 mm
No load speed	1500-4500 rpm
Orbit rate, no load	3000-9000 opm
Power input	710 watt
Power output	420 watt
Cable length	4,0 m
Size (W x L x H)	370 x 40 x 140 mm
Weight	2,4 kg

Standard equipment

1 special velcro backing pad, 125 Ø	487.953
1 special velcro backing pad, 150 Ø	487.988