

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Rotary hammer drill, 2,3 kg, SDS-plus

FHE 2-22 SDS-plus

Order number 413.674



Rotary hammer drill, 2,3 kg, SDS-plus

- + Light-weight and handy 710 watt pistol-shaped fixing hammer
- + Hammer drilling
- + Max.drilling range up to 22 mm in concrete
- + Ideally suited for drilling/hammer drilling, diameter 4-12 mm in concrete for attachment of dowels and anchors
- + Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- + Depth limit gauge: for precision drilling
- + Accelerator switch with lock-on function
- + Robust glass fibre reinforced housing

Technical attributes

| | |
|-------------------------------|-------------------|
| No load speed | 0-1400 rpm |
| Blows per minute | 0-4300 bpm |
| Single impact energy (EPTA) | 2,1 J |
| Max. drill hole Ø in concrete | 22 mm |
| Max. drill hole Ø in steel | 13 mm |
| Max. drill hole Ø in wood | 26 mm |
| Power input | 710 watt |
| Tool fixture | SDS-plus |
| Cable length | 4,0 m |
| Size (W x L x H) | 345 x 80 x 200 mm |
| Weight | 2,3 kg |

Standard equipment

| | |
|-----------------------------|---------|
| 1 handle | 416.126 |
| 1 drill depth stop | 416.118 |
| 1 carrying case L-BOXX® 136 | 414.085 |
| 1 case insert | 414.042 |