

REVOLT X ADVANCED PRO 2



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Gloss Misty Forest/Matte Black Diamond
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
SEATPOST	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SADDLE	Giant Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival 1, 1x11
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Rival 1
BRAKES	SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival 1, left lever dropper switch
CASSETTE	SRAM Rival, 11-speed, 11x42
CHAIN	SRAM PC-1130
CRANKSET	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
HUBS	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TIRES	Giant CrossCut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Recommended Retail Price: \$4,560

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Seat Tube Length (inch)	16.9	17.7	18.5	19.3	20.1	20.9
Seat Tube Angle	74.0° 73.9°	73.5° 73.4°	73.5° 73.4°	73.0° 72.9°	73.0° 72.9°	73.0° 72.9°
Top Tube Length (inch)	21.4	21.8	22	22.6	23	23.6
Head Tube Length (inch)	3.5	3.9	4.5	5.1	5.7	6.3
Head Tube Angle	70.5° 70.4°	71.0° 70.9°	71.5° 71.4°	72.0° 71.9°	72.0° 71.9°	72.0° 71.9°
Fork Rake (inch)	2	2	2	2	2	2
Trail (inch)	3.1 3.3	3 3.1	2.9 3	2.8 2.9	2.8 2.9	2.8 2.9
Wheelbase (inch)	40.3 40.7	40.3 40.7	40.4 40.8	40.6 41	41 41.4	41 41.4
Chain Stay Length (inch)	16.7 17.1	16.7 17.1	16.7 17.1	16.7 17.1	16.7 17.1	16.7 17.1
Bottom Bracket Drop (inch)	2.7 2.7	2.7 2.7	2.7 2.7	2.7 2.7	2.7 2.7	2.7 2.7
Stack (inch)	21.6	22	22.7	23.3	23.9	24.5
Reach (inch)	15.2	15.2	15.3	15.5	15.7	16
Stand Over Height (inch)	28.1 28.3	28.9 29	29.5 29.8	30.2 30.4	30.9 31.2	31.5 31.8
Handlebar Width (inch)	17.3	17.3	18.1	18.1	18.9	18.9
Stem Length (inch)	2	2.4	2.8	3.1	3.1	3.1
Crank Length (inch)	6.7	6.7	6.8	6.8	6.9	6.9
Wheel Size	700C	700c	700c	700c	700c	700c

*All specifications and prices listed are subject to change without notice.