

## Safety vacuum cleaner with automatic filter cleaning system, 42 l, class L

### VCE 44 L AC-Set

Order number 465.690



#### Technical attributes

Power input P. max.	1200 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm <sup>2</sup>
Container volume	42 l
Liquid capacity	26 l
Power take off	100-2400 watt
Cable length	7,5 m
Size (W x L x H)	565 x 385 x 650 mm
Weight	16,7 kg

#### Safety vacuum cleaner with automatic filter cleaning system, 42 l, class L

- + Adapter plate for fixing L-BOXXes and Tanos systainers on the head of the vacuum cleaner
- + The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result
- + Continuous automatic flat filter cleaning ensures no loss of suction
- + The flat-fold filter with Teflon coating / nanocoating allows optimum use of the tank volume
- + With permanent socket and electronic automatic on/off switch
- + The flow rate control via the rotary switch minimises possible vacuums on the surface during intermediate and finish sanding
- + Suitable for wet vacuuming: with electronic liquid level control
- + Soft start stops any voltage peaks at the start and the run-on feature (15 sec. overrun) empties any remaining dust in the vacuum hose
- + Double-walled sturdy container with integrated grip recess for emptying the container easily
- + Dust-protected antistatic finish prevents electric charging of the suction hose
- + Equipped with large wheels and two swivel guide rollers made of metal
- + Separate motor air cooling duct with coarse dirt filter. Protects the turbine against the ingress of ambient air and thereby extends the service life. (Fine dust filter PES available as an accessory)
- + Simple filter change without removing the suction head
- + With hose retainer and expander for easy, quick securing of the power cable
- + With 4 clamping loops (2 on each side) for attaching straps and a giraffe holder
- + Recommendation: When working with a filter bag turn off the automatic cleaning system. When using a disposable bag leave the system on
- + Safety vacuum cleaner, approved for dust class L, suitable for all dust with OEL value >1 mg/m<sup>3</sup>

#### Standard equipment

Antistatic suction hose Ø 32 mm x 4 m with clip connection including auxiliary air control and suction adapter SAD-C D25-32AS	406.708
1 L-BOXX® holder	445.169
1 flat-fold filter PES L/M/H	445.118
1 fleece filter bag class L/M	1 piece of 502.227
1 PP waste disposal bag	1 piece of 445.061
1 adapter Ø 25-32 mm, anti-static	445.029
Hose clip	2 pieces
1 cleaning set	445.053

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### PES flat folded filter

Order number 445.118



#### Technical attributes

QTY/PKG

1

Teflon-coated/nano-coated Class M filter, can also be used for L and H vacuum cleaner. Long service life thanks to high-quality PES filter fleece. The dirt-repelling surface improves the cleaning of the filter material. The filter pores are reliably kept free of dirt. Easy to clean, long service life, also suitable for wet work.

### PES flat folded filter

Order number 445.134



#### Technical attributes

QTY/PKG

1

PES motor cooling air prefilter, cleans the cooling air in particle-loaded area in order to protect the motor. For all classes L/M/H of the 33 and 44 series.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Longlife filter sack

Order number 445.517



#### Technical attributes

QTY/PKG	1
---------	---

Resealable, reusable filter bag made of 3-layer polyester fleece for sucking up coarse dirt.

### Disposal bag

Order number 445.061



#### Technical attributes

QTY/PKG	5
---------	---

Sealable waste bag made of PP, ideal for coarse dirt. For VCE 33/44 L/M AC.

### Handle

Order number 445.150



#### Technical attributes

QTY/PKG	1
---------	---

Easy to mount, for comfortable handling of the vacuum cleaners even when the container is full.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### L-BOXX® holder

Order number 445.169



#### Technical attributes

QTY/PKG	1
---------	---

Adapter plate for securing L-BOXXes and Tanos systainers on the head of vacuum cleaner. For VCE 33/44 L/M/H.

### L-BOXX® Air holder

Order number 445.177



#### Technical attributes

QTY/PKG	1
---------	---

Attachment for using pneumatic devices and for fixing L-BOXXes and Tanos systainers. Regulates the automatic activation when pneumatic devices are used.

## Accessories

### Giraffe holder

Order number 445.185



#### Technical attributes

QTY/PKG	1
---------	---

Support for holding the giraffes GE 5/ GE 5 R can be easily clipped on to the head of the vacuum cleaner VCE 33/44 L/M/H AC.

### Antistatic suction hose with auxiliary air control

Order number 406.708



#### Technical attributes

QTY/PKG	1
---------	---

Internal Ø 32 mm, 4 m with universal device connection, snap connection and universal adapter (445.029), antistatic. Includes variable adjustment of suction power for reduction of vacuum.

## Accessories

### Antistatic suction hose

Order number 379.395



#### Technical attributes

Dimensions in mm	27 Ø x 4m
QTY/PKG	1

Internal Ø 27 mm, 4 m with universal device connection and coupling bush Ø 27 mm with rotary coupling for power tool, antistatic.

### Suction hose extension

Order number 296.953



#### Technical attributes

QTY/PKG	1
---------	---

Suction hose extension with click connection to connect with inside thread adapter i.e. SAD D32-..., SAD D25-32 AS etc.

### Suction hose snap coupling repair kit

Order number 408.697



#### Technical attributes

QTY/PKG	1
---------	---

Coupling bush for suction hose with snap coupling, 3-part. Also suited for antistatic suction hose (electrically conductive). Inclusive with auxiliary air.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Snap-ring grey

Order number 379.654




For suction hose SH-C with snap coupling.

#### Technical attributes

QTY/PKG	1
---------	---

### Clip-on quick clamping ring red

Order number 406.023




For suction adapter SAD-FC 32 and for GE 5 /R, GSE 5 R.

#### Technical attributes

QTY/PKG	1
---------	---

### Threaded ring clip with auxiliary air control

Order number 406.716



Threading 32 mm Ø with snap coupling, inclusive variable auxiliary air adjustment of suction power for reduction of underpressure. Compatible

#### Technical attributes

QTY/PKG	1
---------	---




FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

for suction hose 32 mm.

## Clip adapter

Order number 408.360



### Technical attributes

QTY/PKG	1
---------	---

For connecting a FLEX power tool to extraction units from other manufacturers. Suitable for hoses inside  $\varnothing$  27 mm, outside  $\varnothing$  36 mm, with auxiliary air adjustment.

## Fast clip adapter

Order number 410.497



### Technical attributes

QTY/PKG	1
---------	---

Change adapter on electric power tools with closed FLEX clip-system for quick and easy detachment/attachment (quick clamping ring).



FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Adapter

Order number 445.029



#### Technical attributes

QTY/PKG	1
---------	---

Universal adapter antistatic, for universal connection of machines with 25-32 mm  $\emptyset$  extraction connection with 32 mm suction hose, for adapter with snap connection, can be trimmed to 3 different diameters.

### Adapter

Order number 445.142



#### Technical attributes

QTY/PKG	1
---------	---

Suitable for suction hoses using the FLEX clip-system. Antistatic design.

## Accessories

### Adapter

Order number 382.736



Antistatic sleeve  $\varnothing$  27 mm, with internal thread, suitable for suction hose 379.395.

#### Technical attributes

QTY/PKG	1
---------	---

### Adapter

Order number 259.827



Universal adapter with 32 mm thread inside for universal connection of machines with 25-32 mm  $\varnothing$  extraction connection with 32 mm suction hose (without clip attachment), or with suction hose extension (296.953). Adapter can be trimmed to 3 different diameters.

#### Technical attributes

QTY/PKG	1
---------	---

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Special adapter

Order number 340.790



#### Technical attributes

QTY/PKG	1
---------	---

Suitable for suction hoses with 32 mm  $\emptyset$  without FLEX clip-system and for the suction hose extension (296.953).

### Special adapter

Order number 364.460



#### Technical attributes

QTY/PKG	1
---------	---

Suitable for vacuum hose with FLEX clip-system. Antistatic equipment. For WSE 500 and WS 702 VEA. Note: to attach the extraction connection to WSE 500, WS 702 VEA please order the following articles, snap ring 359.696, clamping nut 359.688.

## Accessories

### Special adapter

Order number 328.308



#### Technical attributes

QTY/PKG	1
---------	---

Adapter 32/32 mm, for connecting a machine with 32 mm  $\emptyset$  vacuum cleaner outlet (e.g. renovation sander or angle grinder with cutting guard) with 32 mm vacuum hose or with suction hose extension (296.953).

### Special adapter

Order number 251.847



#### Technical attributes

QTY/PKG	1
---------	---

Adapter 32/28 mm, for connecting machines with 28 mm  $\emptyset$  vacuum attachment to 32 mm vacuum hose or with suction hose extension (296.953).  
For MS 1706/1709 FR.

## Accessories

### Coupling bush

Order number 257.169



#### Technical attributes

QTY/PKG	1
---------	---

For connection of 32 mm  $\emptyset$  suction hoses and suction hose extension SHV-C 32x0.5 m (296.953) to the device with 36 mm  $\emptyset$  extraction connection.

### Coupling bush

Order number 296.996



#### Technical attributes

QTY/PKG	1
---------	---

For connecting two FLEX vacuum hoses, without connection, inside thread 32 mm.

### Cleaning set

Order number 445.053



#### Technical attributes

QTY/PKG	1
---------	---

Consisting of an antistatic elbow (445.010) for connecting the suction hose and suction pipe, 3 x 350 mm extension pipe INOX (445.207), clip

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

floor nozzle (445.509), round brush (385.646), cushion nozzle (385.549) and joint nozzle (385.530).

## Elbow

Order number 445.010



Technical attributes	
QTY/PKG	1

Antistatic, for connection of suction hose with snap connection and suction tube.

## Extension tube

Order number 445.207



Technical attributes	
QTY/PKG	3

Stainless steel extension pipes, length 3 x 350 mm. For connection to elbow K-C 32 KU AS (445.010).

## Accessories

### Brush nozzle

Order number 385.557



Brush nozzle with brush edge for cleaning sensitive surfaces. Width 46 mm, length 220 mm.

#### Technical attributes

QTY/PKG	1
---------	---

### Round brush

Order number 385.646



Round brush nozzle with brush edge for cleaning sensitive surfaces. Diameter 36 mm, length 120 mm.

#### Technical attributes

QTY/PKG	1
---------	---

### Upholstery nozzle

Order number 385.549



Upholstery nozzle with thread catcher, diameter 36 mm, width 115 mm.

#### Technical attributes

QTY/PKG	1
---------	---



FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Crevice nozzle

Order number 385.530



Crevice nozzle diameter 36 mm, length 300 mm (not serial equipment).

#### Technical attributes

QTY/PKG	1
---------	---

### Surface nozzle

Order number 413.437



The surface nozzle (90x120 mm) made of plastic with bevelled nozzle part is suitable for the suction of dust and loose dirt residues for small repair work for the suction in corners, niches, recesses, window sills that are difficult to reach. Also available as wide crevice tool for the suction of cracks as well as in the interior of vehicles for seat surfaces, gaps and consoles.

#### Technical attributes

QTY/PKG	1
---------	---

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Combination floor nozzle

Order number 385.565



#### Technical attributes

QTY/PKG

1

Switchable combination floor nozzle for cleaning carpeted floors and hard floors. Diameter 36 mm, width 260 mm.

### Floor nozzle with rollers

Order number 369.896



#### Technical attributes

QTY/PKG

1

Aluminium floor nozzle with height-adjustable castors and replacement insert. Inserts: brush insert for dry cleaning and rubber strips for wet cleaning, 370 mm width.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Brush strip

Order number 374.075




Brush strip insert (spare part) for aluminium floor nozzle (369.896)

#### Technical attributes

QTY/PKG	2
---------	---

### Rubber strip

Order number 374.083



Rubber lip insert (spare part) for aluminium floor nozzle (369.896).

#### Technical attributes

QTY/PKG	2
---------	---

### Floor nozzle

Order number 445.509



#### Technical attributes

QTY/PKG	1
---------	---

Brush strip insert for dry cleaning and rubber strip insert for wet cleaning. Diameter 36 mm, width 300 mm.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Clip floor nozzle with rollers

Order number 385.573



#### Technical attributes

QTY/PKG	1
---------	---

Clip floor nozzle with rollers and interchangeable insert. Brush strip insert for dry cleaning and rubber strip insert for wet cleaning. Diameter 36 mm, width 400 mm.

### Brush strip

Order number 385.581



#### Technical attributes

QTY/PKG	2
---------	---

Brush strips (replacement requirement) for the clip floor nozzle (385.573).

### Rubber strip

Order number 385.603



#### Technical attributes

QTY/PKG	2
---------	---

Rubber lips (replacement requirement) for clip floor nozzle (385.573).

## Accessories

### Drill dust adapter

Order number 394.025



#### Technical attributes

Dimensions in mm	290 x 65
QTY/PKG	1

The drill dust extractor is connected to the suction hose of the FLEX vacuum cleaners or to different adapters so that the dust is extracted directly through the drill hole. There is no dust residue. For drilling applications up to  $\varnothing$  24 mm.

### Cable clip

Order number 252.188



#### Technical attributes

QTY/PKG	1
---------	---

For fixing power tool cable to vacuum hose, suitable for 27-36 mm external  $\varnothing$ .

### Rotating vacuum adapter

Order number 340.804



#### Technical attributes

QTY/PKG	1
---------	---

The connector rotates and connects the 32 mm diameter suction hose with its intake fitting. Also suitable for the antistatic suction hose

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

(electrically conductive).

## Cleaning set

Order number 451.703



### Technical attributes

QTY/PKG	1
---------	---

Consisting of 1 carrying case L-BOXX® 102, antistatic elbow (445.010) for connecting the suction hose and suction pipe, 3 x 350 mm extension pipe INOX (445.207), clip floor nozzle (445.509), round brush (385.646), cushion nozzle (385.549) and joint nozzle (385.530).

## Exhaust air set

Order number 477.621



### Technical attributes

QTY/PKG	1
---------	---

Consists of suction hose inner Ø 50 mm, 4 m and VCE exhaust air connector and coded suction hose connection. To remove the cleaned exhaust air from the work area. This prevents hazardous dust from being whirled around and polluting the working environment with more fine respirable dust.

## Accessories

### Cleaning set

Order number 477.613



#### Technical attributes

QTY/PKG	1
---------	---

Comprises suction hose inner-Ø 50 mm, 1,75 m, 2 plastic suction tubes Ø 50 x 510 mm, and 1 coarse dust nozzle Ø 50. To vacuum heavy, coarse dust. By using this D50 cleaning set, the maximum air volume of the suction equipment is used to vacuum heavy dust and particles effectively. The special coarse dust nozzle supports this effect and is designed to take up dirt specifically without a loss in air volume.

### Antistatic suction hose with auxiliary air control

Order number 477.605



#### Technical attributes

QTY/PKG	1
---------	---

Inner-Ø 32 mm, 4 m with clip system grey including bleed air control, antistatic. The suction hose is sheathed in polyester fabric so it slides more easily across edges and uneven surfaces which prevents from abrasion damage. The polyester fabric increases the flexibility of the hose and protects it against solar radiation.



FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Fleece filter bags

Order number 502.227



#### Technical attributes

QTY/PKG	5
---------	---

Class M fleece filter sack. Improved filling compared with paper filter sacks, durable and moisture-resistant. Due to the larger dimensions, the filter sack can be used for both containers 33 and 44.

### Suction hose with auxiliary air control

Order number 445.037



#### Technical attributes

QTY/PKG	1
---------	---

Internal Ø 32 mm, 4 m with universal device connection, snap connection, includes variable adjustment of suction power for reduction of vacuum.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Suction hose

Order number 341.355



Internal Ø 32 mm, 4 m with universal device connection. With special adapter SAD D32 WS/WSK.

#### Technical attributes

QTY/PKG

1

### CordlessConnect system

Order number 512.869



For connecting cordless units to professional corded safety vacuum cleaners. The radio remote control is fixed to the suction hose or battery unit by means of a grid tape, the radio socket is connected to the mains cable and the vacuum cleaner is set to manual operation. The vacuum is activated via the wireless remote control at the touch of a button or automatically via the built-in vibration sensor. Set consisting of radio socket, radio remote control, long and short grid tape (23.5 /13 cm).

#### Technical attributes

QTY/PKG

1