FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com

# FLEX

# 2100 watt angle grinder, 180 mm

# L 21-8 180



### 2100 watt angle grinder, 180 mm

+ Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability

+ Ergonomically designed and very slim motor housing provides optimum guidance and handling. An additinal vibration damping ring between the motor housing and rear handle reduces the vibrations

+ SoftVib handgrip for reduced vibration can be mounted in three positions.

- + Rear shaft handle with soft padding for secure grip
- + Switch: with lock-off / lock-on switch
- + Restart protection after power interruption
- + Soft-start: for a soft start without power overloading
- + Spindle lock
- + Tool-free adjustment of safety guard
- + Disc guard cover for cutting guard (446.718), as an optional accessory

## Order number 392.782

Technical attributes	
Max. disc diameter	180 mm
No load speed	8300 rpm
Power input	2100 watt
Power output	1250 watt
Tool fixture	M 14
Clamping collar Ø	64 mm
Cable length	4,0 m
Size (W x L x H)	495 x 101 x 135 mm
Weight	5,2 kg

### Standard equipment

1 guard grinding 180 Ø	416.517
1 SoftVib handle	325.384
1 clamping flange	338.753
1 clamping nut M14	100.080
1 pin wrench	100.110