Safety Data Sheet (SDS)

	Effective Date: June 1, 2016
1. IDENTIFICATION OF TH	E SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING
Material Name	: SHELL ONDINA OIL 32,67
Recommended Use	: White mineral oil.
Restricted Use	: Other than those above.
Manufacturer/Supplier	: Showa Shell Sekiyu K.K.
	3-2, Daiba 2-chome, Minato-ku, Tokyo, 135-8074, Japan
Telephone/Fax	: Refer to end of this document.
Emergency Telephone	: Refer to end of this document. (Japanese office hours only)
Number	Technical Support Team, Lubricants & Bitumen Division
SDS Code	: 493411

2. HAZARDS IDENTIFICATION GHS Classification : NOT HAZARDOUS GHS Label Elements Symbol(s) : No symbol Signal Words: No signal wordHazard Statement: Not classified under GHS criteria. **GHS Precautionary Statements** : No precautionary phrases. Prevention Response : No precautionary phrases. : No precautionary phrases. : No precautionary phrases. Storage Disposal Unclassified Hazard : Please see Section 4 - 8 before use for Prevention/Response/Storage/Disposal. Used oil may contain harmful impurities. Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance or Mixture	: Substance(UVCB: Unknown or Variable composition, Complex reaction products and Biological materials)
Chemical Description	: Lubricating oil.
Component Information	: Lubricant base oil (White mineral oil) 100%
Chemical Formula	: Not possible to define.
CAS registry number	: Trade secret
Additional Information	: If product contained highly refined mineral oil, it contains <3% DMSO-extract, according to IP346.
Pollutant Release and Transfer	: Not applicable
Register (PRTR) Law	
Industrial Safety and Health	: Not applicable
Law Poisonous and Deleterious	. Natanaliaakla
Substance Control Law	: Not applicable
Classification of components	: [Chemical Identity/Hazard Class (category)/Hazard Statement/Conc.]
according to GHS	No hazardous information.
The specific chemical identities an	d percentages of composition have been withheld as trade secrets.

The specific chemical identities and percentages of composition have been withheld as trade secrets.

4. FIRST AID MEASURES	
General Information	: Not expected to be a health hazard when used under normal conditions.
Inhalation	: Remove casualty to fresh air and keep at rest in a position comfortable for breathing. Cover with blanket to keep warm and rest in a quiet surrounding. Seek immediate medical advice and attention.
Skin Contact	: Wash skin with large amount of water using soap.
Eye Contact	: Rinse cautiously with clean water for several minutes. Remove contact lenses, if present and easy to do, and continue rinsing. After rinsing for a minimum of 15 minutes, seek medical advice and attention.
Ingestion	: Without inducing vomiting, call a doctor for treatment. If mouth has been dirtied, clean with water.
Most Important	: If swallowed, may irritate mucous membrane of stomach and induce vomiting.
Symptoms/Effects, Acute	Inhalation if mist may cause feeling ill. Skin contact and eye contact may cause
& Delayed	irritation.
Immediate Medical Attention, Special Treatment	: Treat symptomatically. Call a doctor or poison control center for guidance.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emerg	jency personnel.
Suitable Extinguishing : Media	Concentrated strong liquid in mist and powder forms, carbon dioxide and foam. Use powder and carbon dioxide may be used small fires only. Effective to use foam to

6. ACCIDENTAL RELEASE MEASURES

0. ACCIDENTAL RELEASE	
	released material. For guidance on selection of personal protective equipment see Section
	3 for information on disposal. Observe the relevant local and international regulations.
Personal Precautions,	: Avoid contact with skin and eyes. Prepare suitable equipment and materials.
Protective Equipment and	
Emergency Procedures	
Environmental	: Use appropriate containment to avoid environmental contamination. Prevent from
Precautions	spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. In event of entering in the sea, extend oil fences to prevent from spreading, and sop up with absorbent materials. Use chemicals and/or detergents, they must satisfy technical standards as set by the Ministry of Land, Infrastructure and Transport / Ministry of the Environment.
Methods and Material for	: Promptly remove all ignition sources and stop leakages. In a small leakage, absorb
Containment and Clean	and recover by use of soil, sand, sawdust and waste clothes. In a large leakage,
Up	cordon off the danger zone, prevent from entering and enclose it with sand bank and
	stop outflow. Cover liquid surface with foam, and recover liquid into containers.
Additional Advice	: Local authorities should be advised if significant spillages cannot be contained.
7. HANDLING AND STORAG	GE CONTRACTOR
HANDLING	
Technical Messures	
Technical Measures	: In handling this material over the allocated volume, ensure approval to meet requires of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting.
Ventilation Precautions	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8
	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact
Ventilation Precautions Precautions for Safe Handling	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8
Ventilation Precautions Precautions for Safe	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials.
Ventilation Precautions Precautions for Safe Handling	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct
Ventilation Precautions Precautions for Safe Handling STRAGE	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials.
Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct
Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and
Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation.
Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage Technical Measures Precautions for Safe	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. All electrical appliances shall be explosion-proof types, and they all must be earthed. Avoid contact and storage in same place with halogens, strong acids, alkali and
Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage Technical Measures	 the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. All electrical appliances shall be explosion-proof types, and they all must be earthed. Avoid contact and storage in same place with halogens, strong acids, alkali and oxidizing materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference provided for information only	of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is v.
Equipment	: Seal or install ventilations for mist occurs. Install eye shower and body shower near working site.
Standard Concentration Control	: Not specified
OSHA, Permissible	: 5mg/m ³ (as Oil mist, mineral)
Exposure Limits (PEL)	
Occupational Exposure Limits	: Japan Society for Occupational Health(2012) ⁽¹⁾ Data not available. ACGIH(2012) TWA[Inhalable fraction.] ⁽²⁾ Data not available.
	ACGIH(2012) TWA[Inhalable fraction.] ⁽²⁾ Data not available.

 Protective Equipment
 : Skin protection not ordinarily required beyond standard issue work clothes.

 Respiratory Protection
 : No respiratory protection is ordinarily required under normal conditions of use. Use appropriate equipment in response to the circumstances.

Hand Protection: Use oil-proof protective hand gloves under prolonged or repeated skin contact.Eye Protection: Wear safety glasses or full face shield if splashes are likely to occur.

Skin and Body Protection	: Use oil-proof/long sleeved clothing under prolonged usage.
Appropriate Sanitary Measures:	: Remove immediately all contaminated clothing. Contaminated clothing must be laundered before reuse.

9. PHYSICAL AND CHEMIC	AL PROPERTIES	. Liquid at room town areturn
Physical state		: Liquid at room temperature.
Colour		: Colourless. Clear.
Odour Odour thread old		: Characteristic mineral oil
Odour threshold		: Data not available.
pH Initial Bailing Baint		: Not applicable.
Initial Boiling Point		: Expected >250°C : <-10°C
Pour point		
Flash point Flammability of the produc		: ≥ 200°C (COC) : Flammable.
Upper / lower Flammability		: Typical 1 - 7 %(V) (based on mineral oil)
Auto-ignition temperature		: Data not available. Expected >320°C
Density		: Approx. 0.86g/cm ³ (15°C)
Solubility		: Water: Negligible.
Decomposition Temperatu	re	: Data not available
Vapour pressure		: Data not available
Vapour density		: Data not available. Expected >1
n-octanol/water partition c	oefficient (log Pow)	: Data not available
Evaporation rate		: Data not available
Evaporation rate		
10. STABILITY AND REACT	Ίνιτγ	
Chemical Stability	: Stable under normal of	condition.
Hazardous Reactivity		
Conditions to Avoid		logens, strong acids, alkalis, and oxidizing materials.
Incompatible Materials	: Data not available.	
		ition products are not expected to form during normal storage.
Products		rbon monoxide, sulfurous acid gas etc. during combustion.
11. TOXICOLOGICAL INFO	RMATION	
Basis for Assessment	Information given is bas	ed on data on the components and the toxicology of similar
	products.	
	Unless indicated otherw	ise, the data presented is representative of the main component
		er than for individual component(s). Individual components
	contained above cut-off	value is described on Section 3.
Acute Toxicity	1 Oral E	Expected to be of low toxicity: LD ₅₀ > 15,000 mg/kg , Rat
-	2 Dermal E	expected to be of low toxicity: LD ₅₀ > 5,000 mg/kg , Rat
	3 Inhalation(Vapour) E	Data not available
		Data not available
Skin Corrosion/Irritation	: Not classified as a ski	n irritation (rabbit test).
Serious Eye	: Not classified as an e	ye irritation (rabbit test).
Damage/Irritation		
Respiratory or Skin	: No data available con	cerning respiratory sensitisation.
Sensitisation	Not classified as a ski	n sensitiser (pig test).
Germ Cell Mutagenicity	: Data not available.	
Carcinogenicity		oils are not classified as carcinogenic by the International
		on Cancer (IARC monographs: Group 3). White mineral oils are
		efining and not classified as a carcinogen.
Reproductive and		productive and Developmental Toxicity (rabbit test, 4,350mg/kg·
Developmental Toxicity	bw/day, 5days a weeł	
Specific target organ	: Not expected to be a	hazard.
toxicity		
Aspiration Hazard		drocarbon with kinetic viscosity \leq 20.5mm2/s measured at 40°C.
	Not considered an as	piration hazard.
40 5001 001041 1150555		
12. ECOLOGICAL INFORM		encounter the second strength and successful the state of
Basis for Assessment		ave not been determined specifically for this product.
		ed on a knowledge of the components and the ecotoxicology of
	similar products.	the data management of the second state of the
		rise, the data presented is representative of the main component
		er than for individual component(s). Individual components
Coutien		value is described on Section 3.
Caution		e. May cause physical fouling of aquatic organisms.
Acute Aquatic Toxicity	: Fish Practically r	non toxic: LC50>10,000mg/L (Lepomis macrochirus, 96hrs)

· · · · · · · · · · · · · · · · · · ·	 Not expected to be a hazard. Generally floats on water. Lubricating oil components have estimated log Koc >3, indicating these components are likely to be adsorbed onto soil and sediment and are not likely to leach to ground water. Data not available Data not available Not classified because this product not contained substances listed on Montreal Protocol and Ozone Layer Protection Law. 		
13. DISPOSAL CONSIDERA	TIONS		
Material Disposal	 Waste disposal yourself or entrust the industrial waste treatment company who obtained the prefectural governor's permission or municipal corporation. Disposal should be in accordance with applicable regional, national, and local laws and regulations. Do not dispose into the environment, in drains or in water courses. For landfill disposal, destroy by fire and confirm cinders agreed to Waste Disposal Law. In event of burning this material, ensure to carryout work in safe place with guards in 		
	position, and select a method that would not cause any harm or damage to others		
Container Disposal	during combustion or explosion.Purify and recycle or performs suitable disposal in accordance with the standard of related laws and regulations. Disposal with remove content completely.		
14. TRANSPORT INFORMAT	ION		
International Restriction UN Class, Shipping Name	: Not Dangerous Goods.		
UN Number	: Not applicable.		
Marine Pollutant	: Yes.		
Other Information	: This material is not classified as dangerous under IMDG/IATA regulations.		
Domestic Restriction	: Since domestic laws and regulations shown below are applicable, containers and transportation methods shall be required to follow each and even regulation		
Land Fire Service Law Container:	 transportation methods shall be required to follow each and every regulation. Dangerous goods. Group 4 (flammable liquid), Class 4 petroleum, Danger grade III If product classified as dangerous goods, use containers (other than tanker, tank car and tank truck) for transportation usage, shall meet the Clause 2, Notice Attachment 3, concerning dangerous materials. 		
Sea	: Ship Safety Law: Not Dangerous Goods.		
Air	: Civil Aeronautics Act: Not Dangerous Goods.		
Specific safety measures and conditions for	 Caution: Flammable. Transport remarkably with containers may not cause friction or agitation. 		
transportation	 3 Display signage on vehicle and provide with fire fighting equipment, if and when required to transport more than the specified quantity. Total piled height of vehicle shall 		
	be less than 3 meters.		
	4 Consolidation of this material with dangerous goods belonging to the 1st and 6th		
	Classification is prohibited.		
	5 Abide by other laws and regulations that are applicable.		
15. REGULATORY INFORMA International Information			
EINECS/ELINCS (EC)	: All components listed or polymer exempt.		
TSCA (USA) METI (JAPAN)	All components listed or in compliance.All components listed or in compliance.		
Domestic Information			
Fire Service Law	: Dangerous goods. Group 4 (flammable liquid), Class 4 petroleum, Danger grade III		
Pollutant Release and Transfer Register (PRTR) Law	: Not applicable		
Industrial Safety and Heal Law	Ith : Not applicable		
Poisonous and Deleteriou Substance Control Law			
Marine Pollution Protection	on : Waste Oil Regulation.		
Sewage Control Law Water Pollution Preventio Law	: Mineral Oil Disposal Regulation. (5mg/L) on : Oil Disposal Regulation. (5mg/L)		
Waste Disposal and Publi	ic : Industrial Waste Regulation.		

SHELL ONDINA OIL 32,67 Code:493411 Date:June 1, 2016 Page:4/5

Cleaning Law

16. OTHER INFORMATION

- Subscribe "%" in this document means weight percentage.

[Quotation]

- 1. Recommendation of Occupational Exposure Limits (2012), Japanese Society of Occupational Health
- 2. Thresholds limit values for chemical substances and physical agents and biological exposure indices, ACGIH (2012)
- [Reference]
- Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 4th revised edition, UNITED NATIONS(2011)
- Japanese Standards Association (JSA), JIS Z 7253:2012, JIS Z 7252:2014
- National Institute of Technology and Evaluation (nite), "GHS Information"
- Ministry of Economy, Trade and Industry, Chemical Management site.
- Ministry of Health, Labour and Welfare, "Label and MSDS information for GHS model"

Safety Data Sheet (SDS) about hazardous chemical is provided for a entrepreneur as reference information for safety handling. Refer to this document and perform suitable handling. Nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use. There is no warranty against intellectual property infringement. The information contained in this document is based upon data believed to be reliable through our supply chain at the time. So, Showa Shell Sekiyu could not guarantee all about the contents. This document is based on JIS Z7253:2012, and is not a guarantee of safety. Contents of SDS updated periodically. SDS compliance is required as a rule to all business enterprises engaged in transaction of chemicals (including products containing them) with other businesses. Retailer/ Wholesaler must provide newest SDS to customers.

[SDS Author]	Showa Shell Sekiyu K.K. / Technical Support Team, Lubricants & Bitumen Division TEL.+81-3-5531-5766, FAX.+81-3-5531-5768
[SDS Request]	As a rule, the direct delivery entrepreneur must provide the newest SDS to customer. Please contact not directly manufacturer but your supply chain company.
[Technical contact]	Showa Shell Sekiyu K.K. / Lubricant Customer Service Center TEL.0120-064-315 (Japanese domestic only) / lub-csc@showa-shell.co.jp