## SMART LIGHT | DOWNLIGHT/RECESSED | WHITE | NOrd ux®





Voltage (V): 230 Volt IP degree if the fixture includes two types of IP degree: IP65 Class (Class I, Class II, Class III): Class 2 (Double isolated) Lampholder type (eg, E27/E14, etc): LED Module

Primary material: Plastic Secondary material: Metal Color: White

Built In Spot Diamter (cm): 8.5 Mount directly into insulation: False

EAN: 5704924003004 TUN: 2116038 Item Number: 2015650101 Pcs Per Master Carton: 6 Sales Box Height (cm): 13

Sales Box Width(cm): 13 Sales Box Depth (cm): 7 Sales Box Volume m³: 0.0012 Net weight of the luminiare (kg):

Useful Lumen (lm): 360 Color Temperature (K): 2200-

6500 Ra-value: 80 Lifetime (h): 20000

Spread Angle (°) (beam angle of

luminaire): 36

Candela (cd) (for directional

lamp only): 0 Energy Class: G

- Twist-lock for easy mounting of smart bulbs Bluetooth connection to Nordlux SmartLight
- Retrofit smart GU10 bulb included IP 65 protection for both outdoor and bathroom use

Carina is a retrofit downlight for indoor use with a die-cast frame and a Smart Light Bulb. Carina is quick and easy to assemble via a screwless connector and twist-lock system.

The Dorado downlight is integrated with the newest Bluetooth Mesh technology allowing you to easily manage the light setting using your selected device. No matter whether you are inside or outside the Bluetooth will allow for a stable communication between your light and device.