

## Wall chaser for push and pull cutting

### MS 1706 FR Set

Order number 329.673



#### Technical attributes

Cutting depth	0-35 mm
Groove width	10-30 mm
Disc Ø	140 mm
No load speed	7500 rpm
Power input	1400 watt
Power output	950 watt
Tool fixture	M 14
Cable length	4,0 m
Size (W x L x H)	410 x 180 x 250 mm
Weight	4,6 kg

#### Wall chaser for push and pull cutting

- + Microprocessor electronics: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- + Patented swivel-mounted motor (EP1693169) allows for push and pull cutting.
- + Optimal dust extraction and maximum safety due to enclosed guard
- + Tool-free blade changing and slit width adjustment
- + Rotating adaptor for dust extractor
- + Tool-free cutting depth adjustment
- + Plunge cut stop
- + Chases two parallel slots up to 35 mm deep and 30 mm wide
- + Slot breaker for easy removal of the remaining material without a hammer
- + This machine is also available in 110 V

#### Standard equipment

2 Diamantjet VI-Speedcut-cutting disc 140 mm Ø	334.464 (2x)
1 side handle	194.034
1 SDS-Clic quick-clamp nut M 14	253.049
Distance spacers	251.478 (1x)
Stacking discs	318.914 (2x)
Clamping flanges	191.612 (2x)
1 web remover	229.253
1 extraction adapter	408.360
Cable clip	252.188 (3x)
1 carrying case	327.034