

Compact vacuum cleaner with manual filter cleaning, 6 l, class L

VC 6 L MC 18.0

Order number 481.491

FLEX

Technical attributes

i cennear aren ibareo	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. volume flow	1400 l/min
Max. vacuum	12000 Pa
Filter surface	3000 cm ²
Container volume	6 l
Size (W x L x H)	240 x 200 x 400 mm
Weight including accessories, w/o battery	3,3 kg

Standard equipment

• •	
1 suction hose 32 mm Ø x 0,5-2,5 m	487.295
1 flat-fold filter class L	488.151
1 fleece filter bag class L	487.287
1 hand pipe	487.198
1 crevice nozzle	487.201
1 round brush	487.228
1 upholstery nozzle	487.236
1 polstered shoulder strap	487.244

+ Very compact, handy and light vacuum cleaner with carrying strap for mobile use. The

Compact vacuum cleaner with manual filter cleaning, 6 l, class L

compact design means it fits in all vehicles

+ The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result

+ By actuating manual filter cleaning, dust deposited in the filter element is removed by a targeted blast of air

+ Flat-fold filter for optimised cleaning and improved container filling

+ Accessories can be stowed due to integrated brackets on the suction head

+ With 32 mm diameter compact hose with a length of 0.5 m can be extended to 2.5 m. Very handy, for easy transport of the vacuum cleaner

+ Easy-to-fit running gear available as an accessory

+ Powerful vacuum cleaner for professional use in final assembly, automotive cleaning etc. FLEX power tools can be connected with ease using the FLEX clip system for extraction work
+ Optimised for cleaning work in offices, storage rooms, workshops and vehicles

+ Eco mode, extends the battery runtime to up to 30 minutes with a max. vacuum of 12 000 Pa

+ FLEX battery system: suitable for all FLEX 18,0 V battery packs. Delivery does not include battery and charger

Accessories

Hand pipe



Order number 487.198

Technical attributes	
QTY/PKG	1



With clip connection.

Threaded ring clip with auxiliary air control



Order number 487.171

Technical attributes		
QTY/PKG	1	

Threadring 32 mm Ø with snap coupling, inclusive variable auxiliary air adjustment of suction power for reduction of underpressure. Compatible for suction hose 32 mm.

Accessories

Suction hose with auxiliary air control

Suction hose with a length of 0.5 m, can be extended to 2.5 m. Internal diameter of 32 mm with universal device connection, hand pipe, clip system, including bleed air control to reduce the suction vacuum as required.

Fleece filter bag

Long-life fleece filter bag class L. Improved filling compared to paper filter bags.

Order number 487.287

	01001 110111001 407.20
Technical attributes	
QTY/PKG	5

Technical attributes

QTY/PKG



FLEX

1

Order number 487.295

Accessories

Flat folded filter



Class L paper flat-fold filter. Dirt-repellent surface and long lifetime.

Flat folded filter



Class M paper flat-fold filter. Dirt-repellent surface and long service life.

Flat folded filter



FLEX

Order number 488.151

Technical attributes		
QTY/PKG	1	

Order number 487.260

Technical attributes		
QTY/PKG	1	

Order number 487.279

Technical attributes		
QTY/PKG	1	

Paper flat-fold filter of class H/HEPA 13. Made from special material with a permeability of < 0.005%. Dirt-repellent surface and long service life.

Accessories

Polstered shoulder strap



Carrying strap for mobile use for the VC 6.

Crevice nozzle



Crevice nozzle diameter 36 mm, length 300 mm.

Upholstery nozzle



Upholstery nozzle, diameter 36 mm, width 115 mm.

FLEX

Order number 487.244

Technical attributes		
QTY/PKG	1	

Order number 487.201

Technical attributes		
QTY/PKG	1	

Order number 487.236

Technical attributes		
QTY/PKG	1	

Accessories

Round brush



1

FLEX



Round brush nozzle with brush edge for cleaning sensitive surfaces. Diameter 36 mm, length 120 mm.

Running gear



Order number 487.252

Technical attributes		
QTY/PKG	1	

Technical attributes

QTY/PKG

Running gear for the VC 6, easy-to-fit.

Rapid charger



Order number 417.882

Technical attributes		
QTY/PKG	1	

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10,8 V approx.



40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.

Power 55 R



Order number 491.349

Technical attributes		
QTY/PKG	1	

Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.

Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

Order number 491.357

Technical attributes		
QTY/PKG	1	

Accessories

Li-Ion rechargeable battery pack 18,0 V

18V inna less

Order number 445.886

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

FLEX

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Li-Ion rechargeable battery pack 18,0 V



Order number 445.894

Technical attributes	
Battery capacity	5,0 Ah
Battery voltage	18,0 V
Weight	0,72 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Accessories

Cleaning set

Order number 512.621



Consisting of suction hose inside Ø 32 mm x 1.5 m with bayonet connection, threaded ring clip with secondary air control (487.171), red clip quick-release ring (406.023), 3 x 360 mm extension tube made of plastic, hand tube K-C 32 HT (487.198) and a combination floor nozzle with brush and rubber strip. For hard and soft floor coverings, suitable for the VC 6 L MC.

