

### Cordless fan 18.0 V

# CF 18.0/230



### Cordless fan 18.0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Stepless air volume regulation
- + Soft start
- + Flexible use thanks to a hook, a 1/4" and 5/8" mount and a head that can be swivelled through  $180^\circ$
- + Can be operated with a 18.0 V battery or via the 230 V power supply unit
- + Running time at maximum speed: approx 2,2 hours with 2.5 Ah battery pack and approx 4,5 hours with 5.0 Ah battery pack
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18,0 V battery packs. Delivery does not include battery and charger

#### Order number 503.002

Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. air speed	4,9 m/sec
Max. air flow rate	18,25 m³/min
Sound pressure level	70 dB(A)
Mains voltage V / frequency Hz	230 V / 50+60 Hz
Connection thread	1/4", 5/8"
Size (W x L x H)	213 x 304 x 400 mm
Weight without battery	2,5 kg

Standard equipment		
1 power supply unit 230 V 50/60 Hz	1 piece	



### **Accessories**

## Li-Ion rechargeable battery pack 18,0 V



#### **Order number 445.886**

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

# Li-Ion rechargeable battery pack 18,0 V



### **Order number 445.894**

Technical attributes	
Battery capacity	5,0 Ah
Battery voltage	18,0 V
Weight	0,72 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.



### **Accessories**

## **Rapid charger**



**Order number 417.882** 

Technical attributes		
QTY/PKG	1	

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10,8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.

## Power 55 R



Order number 491.349

Technical attributes		
QTY/PKG	1	

Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.



## Accessories

## Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

### Order number 491.357

Technical attributes	
QTY/PKG	1