## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or	r trade mark:	PHILIPS
--------------------	---------------	---------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier:	9290023701
-------------------	------------

Type	of I	ight	sour	ce:
IVDC	<b>v</b> ı .	15116	JUUI	···

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Product parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
Energy consur mode (kWh/10 up to the neare	00 h), rounded	2	Energy efficiency class	F	
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	136 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	1,4	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	97	Spectral power dis-	See image	
sions without	Width	35	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	35	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime-					
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	15		
		Chromaticity coordinates (x and y)	0,458 0,410		
Parameters for LED and OLED	Parameters for LED and OLED light sources:				
R9 colour rendering index valu	ue 0	Survival factor	0,90		
the lumen maintenance facto	r 0,93				
Parameters for LED and OLED	mains light sources:				
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent lig source without integrated by last of a particular wattage.	ht	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

