

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Cordless rotary polisher 18.0 V

**PE 150 18.0-EC**

**Order number 459.062**



### Cordless rotary polisher 18.0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + LED battery capacity display
- + Continuous speed control trigger: for a gentle start and a lock-on for continuous operation
- + Innovative combination of planetary and angular gears reduces noise to an absolute minimum
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + Spindle lock: It is ideally positioned to prevent operating error and does not interfere with the grip area.
- + With rubberised resting bar for safe setting down
- + Polishes with low speed and high torque, e. g. for heat-sensitive surfaces
- + Ideal for automotive, maritime and aviation applications
- + FLEX battery system: suitable for all FLEX 18,0 V battery packs. Delivery does not include battery and charger

#### Technical attributes

|                             |                   |
|-----------------------------|-------------------|
| Max. polishing pad diameter | 160 mm            |
| Max. back-up pad diameter   | 150 mm            |
| No load speed               | 150-1450 rpm      |
| Battery voltage             | 18 V              |
| Battery capacity            | 2,5 / 5,0 Ah      |
| Size (W x L x H)            | 395 x 84 x 117 mm |
| Weight without battery      | 1,9 kg            |

#### Standard equipment

|                             |         |
|-----------------------------|---------|
| 1 velcro pad 150 Ø          | 350.745 |
| 1 handle                    | 252.721 |
| 1 carrying case L-BOXX® 238 | 414.093 |
| 1 case insert               | 459.534 |

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polish

Order number 443.271



| Technical attributes |        |
|----------------------|--------|
| Contents             | 250 ml |
| QTY/PKG              | 1      |

Universal high-performance abrasive paste with maximum removal rate for maximum gloss. Sanding grooves of grain size P 1500 can be removed in seconds. Ideally suited for all paint types, including scratch-resistant paints, UV paints and for treating gliders and motorized aircraft, boat hulls, polycarbonate and wood finishing work. The polish is free of wax, silicone and odorant solvents. Minor holograms might be caused by rotary working on dark paints. These can be polished out with the polish P 03/06-LDX in conjunction with the orange polishing sponge PS-0. Abrasiveness 5 / gloss 5.

### Polish

Order number 443.298



| Technical attributes |        |
|----------------------|--------|
| Contents             | 250 ml |
| QTY/PKG              | 1      |

Special polish for removing scratches with a very deep sheen. Sanding grooves of grain size P 2000 can be removed in seconds. Ideal for all paint types, including scratch-resistant paints, UV paints and for freshening up colours in the case of old paints. Optimum results are achieved with eccentric 1-step working, and rotary working is of course also possible. The polish is silicone-free, produces little dust and can be easily rubbed in and wiped off. Abrasiveness 3 / gloss 6.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Sealing

Order number 443.301



#### Technical attributes

|          |        |
|----------|--------|
| Contents | 250 ml |
| QTY/PKG  | 1      |

Paintwork-compatible sealant for new and previously polished paints. It's Carnauba wax protects paint against environmental influences, provides care and protects the high sheen. The sealant can be applied both with a machine (rotary/eccentric) using the red polishing sponge PS-R and manually with the red application sponge PUK-R. It contains no abrasive particles and can be painted over. Protective effect 2 / smoothness 4.

### Microfibre polishing cloth, classic

Order number 317.098



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 400 x 400 |
| QTY/PKG          | 1         |

Seamless, washable. For gentle removal of polishing and sealing residues. For a perfect surface finish and brilliant deep gloss.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Microfibre polishing cloth, premium

Order number 376.531



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 400 x 400 |
| QTY/PKG          | 1         |

Thanks to the very high soft pile, residues can be picked up reliably and gently. This is what makes the microfibre cloth ideal for an optimum paint finish. It can also be used for car wash purposes. Long service life, washing machine safe (without softener).

### Polishing sponge

Order number 442.682



#### Technical attributes


|                  |       |
|------------------|-------|
| Dimensions in mm | 130 Ø |
| QTY/PKG          | 1     |

The red sponge for hand application is ergonomically shaped and has a very soft foam with a fine texture. It is ideally suited to working with sealants and care agents on painted and plastic surfaces, for hard-to-reach places or sensitive surfaces that are difficult to deal with by using a machine.

## Accessories

### Velcro pad, cushioned M 14

Order number 446.254



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing.

#### Technical attributes

|                  |      |
|------------------|------|
| Dimensions in mm | 35 Ø |
| QTY/PKG          | 1    |

### Velcro pad, cushioned M 14

Order number 420.492



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing.

#### Technical attributes

|                  |      |
|------------------|------|
| Dimensions in mm | 75 Ø |
| QTY/PKG          | 1    |

### Velcro pad, cushioned M 14

Order number 240.311



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing cover up to 12.000 rpm (115) / 7.500 rpm (125). Not for LE

#### Technical attributes

|                  |       |
|------------------|-------|
| Dimensions in mm | 115 Ø |
| QTY/PKG          | 1     |

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

15-11 125/LBE 17-11 125.

## Velcro pad, cushioned M 14



### Technical attributes

| Dimensions in mm | QTY/PKG | Order number |
|------------------|---------|--------------|
| 125 Ø            | 1       | 350.737      |
| 150 Ø            | 1       | 350.745      |

12 mm cell rubber for even pressure distribution for grinding, polishing or sealing cover up to 12.000 rpm (115) / 7.500 rpm (125). Not for LE 15-11 125/LBE 17-11 125.

## Polishing sponge

**Order number 442.631**



### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 40 Ø x 25 |
| QTY/PKG          | 2         |

The green sponge has a very hard foam with an innovative X-Cut surface that guarantees a constant and evenly high removal rate. The X-Cut texture reduces the building-up of heat. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 434.264



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 80 Ø x 25 |
| QTY/PKG          | 2         |

The green sponge has a very hard foam with an innovative X-Cut surface that guarantees a constant and evenly high removal rate. The X-Cut texture reduces the building-up of heat. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

### Polishing sponge

Order number 434.272



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 135 Ø x 25 |
| QTY/PKG          | 1          |

The green sponge has a very hard foam with an innovative X-Cut surface that guarantees a constant and evenly high removal rate. The X-Cut texture reduces the building-up of heat. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.



FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 434.280



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 160 Ø x 25 |
| QTY/PKG          | 1          |

The green sponge has a very hard foam with an innovative X-Cut surface that guarantees a constant and evenly high removal rate. The X-Cut texture reduces the building-up of heat. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

### Polishing sponge

Order number 434.299



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 200 Ø x 25 |
| QTY/PKG          | 1          |

The green sponge has a very hard foam with an innovative X-Cut surface that guarantees a constant and evenly high removal rate. The X-Cut texture reduces the building-up of heat. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.



FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 442.658



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 40 Ø x 25 |
| QTY/PKG          | 2         |

The violet sponge has a hard foam for optimum cooling and guarantees a constant and evenly high removal rate. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

### Polishing sponge

Order number 434.442



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 80 Ø x 25 |
| QTY/PKG          | 2         |

The violet sponge has a hard foam for optimum cooling and guarantees a constant and evenly high removal rate. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 434.450



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 135 Ø x 25 |
| QTY/PKG          | 1          |

The violet sponge has a hard foam for optimum cooling and guarantees a constant and evenly high removal rate. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

### Polishing sponge

Order number 434.469



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 160 Ø x 25 |
| QTY/PKG          | 1          |

The violet sponge has a hard foam for optimum cooling and guarantees a constant and evenly high removal rate. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 436.410



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 200 Ø x 25 |
| QTY/PKG          | 1          |

The violet sponge has a hard foam for optimum cooling and guarantees a constant and evenly high removal rate. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

### Polishing sponge

Order number 442.666



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 40 Ø x 25 |
| QTY/PKG          | 2         |

The orange sponge has a medium-hardness foam with a fine foam texture. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with holograms, matting, scratches and car wash traces in conjunction with the P 03/06-LDX.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 434.302



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 80 Ø x 25 |
| QTY/PKG          | 2         |

The orange sponge has a medium-hardness foam with a fine foam texture. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with holograms, matting, scratches and car wash traces in conjunction with the P 03/06-LDX.

### Polishing sponge

Order number 434.310



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 135 Ø x 25 |
| QTY/PKG          | 1          |

The orange sponge has a medium-hardness foam with a fine foam texture. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with holograms, matting, scratches and car wash traces in conjunction with the P 03/06-LDX.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 434.329



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 160 Ø x 25 |
| QTY/PKG          | 1          |

The orange sponge has a medium-hardness foam with a fine foam texture. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with holograms, matting, scratches and car wash traces in conjunction with the P 03/06-LDX.

### Polishing sponge

Order number 434.337



#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 200 Ø x 25 |
| QTY/PKG          | 1          |

The orange sponge has a medium-hardness foam with a fine foam texture. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with holograms, matting, scratches and car wash traces in conjunction with the P 03/06-LDX.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 442.674



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 40 Ø x 25 |
| QTY/PKG          | 2         |

The red sponge has a very soft foam with a fine foam texture. The special PerfectTouch sandwich structure with an additional stronger white foam layer gives the sponge greater rigidity. This configuration increases the service life of the polishing disk. Ideal for dealing with holograms and slight matting in conjunction with the P 03/06-LDX, for paintwork care and sealing in conjunction with the W 02/04.

### Polishing sponge

Order number 434.345



#### Technical attributes

|                  |           |
|------------------|-----------|
| Dimensions in mm | 80 Ø x 25 |
| QTY/PKG          | 2         |

The red sponge has a very soft foam with a fine foam texture. The special PerfectTouch sandwich structure with an additional stronger white foam layer gives the sponge greater rigidity. This configuration increases the service life of the polishing disk. Ideal for dealing with holograms and slight matting in conjunction with the P 03/06-LDX, for paintwork care and sealing in conjunction with the W 02/04.



FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 434.353



The red sponge has a very soft foam with a fine foam texture. The special PerfectTouch sandwich structure with an additional stronger white foam layer gives the sponge greater rigidity. This configuration increases the service life of the polishing disk. Ideal for dealing with holograms and slight matting in conjunction with the P 03/06-LDX, for paintwork care and sealing in conjunction with the W 02/04.

#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 135 Ø x 25 |
| QTY/PKG          | 1          |

### Polishing sponge

Order number 434.361



The red sponge has a very soft foam with a fine foam texture. The special PerfectTouch sandwich structure with an additional stronger white foam layer gives the sponge greater rigidity. This configuration increases the service life of the polishing disk. Ideal for dealing with holograms and slight matting in conjunction with the P 03/06-LDX, for paintwork care and sealing in conjunction with the W 02/04.

#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 160 Ø x 25 |
| QTY/PKG          | 1          |



FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing sponge

Order number 434.426



The red sponge has a very soft foam with a fine foam texture. The special PerfectTouch sandwich structure with an additional stronger white foam layer gives the sponge greater rigidity. This configuration increases the service life of the polishing disk. Ideal for dealing with holograms and slight matting in conjunction with the P 03/06-LDX, for paintwork care and sealing in conjunction with the W 02/04.

#### Technical attributes

|                  |            |
|------------------|------------|
| Dimensions in mm | 200 Ø x 25 |
| QTY/PKG          | 1          |

### Velcro backed, classic



The pad consists of 90 % lambswool and 10 % polyester. This composition provides for more stability and volume. For great polishing effect in combination with the fine polishing compound.

#### Technical attributes

| Dimensions in mm | QTY/PKG | Order number |
|------------------|---------|--------------|
| 150 Ø            | 1       | 342.521      |
| 200 Ø            | 1       | 350.265      |

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Polishing lambswool, premium



Polishing lambswool consisting of 90% natural wool and 10% polyester. This combination provides for longer service life and greater volume. And it can remove sanding scratches, for example, 30% faster than with using a sponge. Ideal for UV paints and the latest generation of scratch-resistant paints. For a great polishing effect in combination with the fine polishing compound. The special PerfectTouch sandwich design and extra orange foam layer gives the pad that slight degree of cushioning and much greater stiffness. This allows for a perfect surface contact even in problem areas and an optimal and exact guiding.

#### Technical attributes

| Dimensions in mm | QTY/PKG | Order number |
|------------------|---------|--------------|
| 80 Ø             | 1       | 420.484      |
| 140 Ø            | 1       | 376.515      |
| 160 Ø            | 1       | 376.523      |

### Backed fleece



Fibre-back and M 14 threaded flange for removing scratches in glass, stainless steel, acrylic and high-gloss polishing of stainless steel. Use only with the respective polishing mediums.

#### Technical attributes

| Dimensions in mm | QTY/PKG | Order number |
|------------------|---------|--------------|
| 125 Ø            | 1       | 122.726      |
| 175 Ø            | 1       | 122.734      |

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Spare fleece




With fiber backing.

#### Technical attributes

| Dimensions in mm | QTY/PKG | Order number |
|------------------|---------|--------------|
| 125 Ø            | 1       | 122.742      |
| 175 Ø            | 1       | 122.750      |

### Case insert



Matching insert for PE 150 18.0-EC for carry case L-BOXX® 238.

**Order number 459.534**

#### Technical attributes

|         |   |
|---------|---|
| QTY/PKG | 1 |
|---------|---|

### Carrying case L-BOXX®



**Order number 414.093**

#### Technical attributes

|                               |                    |
|-------------------------------|--------------------|
| External dimensions L x W x H | 442 x 357 x 253 mm |
| Internal dimensions L x W x H | 378 x 306 x 209 mm |
| Weight                        | 2,8 kg             |
| QTY/PKG                       | 1                  |

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

## Li-Ion rechargeable battery pack 18,0 V

Order number 445.886



| Technical attributes |         |
|----------------------|---------|
| Battery capacity     | 2,5 Ah  |
| Battery voltage      | 18,0 V  |
| Weight               | 0,42 kg |
| QTY/PKG              | 1       |

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

## Li-Ion rechargeable battery pack 18,0 V

Order number 445.894



| Technical attributes |         |
|----------------------|---------|
| Battery capacity     | 5,0 Ah  |
| Battery voltage      | 18,0 V  |
| Weight               | 0,72 kg |
| QTY/PKG              | 1       |

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Rapid charger

Order number 417.882



#### Technical attributes


QTY/PKG

1

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10.8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.

### Extension set for rotary polisher

Order number 458.813



#### Technical attributes

QTY/PKG

1 set

Rotary polisher extensions to facilitate work in narrow and difficult to reach areas such as exterior mirrors, spoilers, bumpers, etc. Comprises three M14 anodized aluminium extensions in 50 mm, 80 mm, 120 mm and one M14 adapter for cordless screwdrivers. Shaft Ø 19 mm, width across flat SW 17, max. backing pad Ø 75 mm, max. polishing disc Ø 80 mm. Packaged in the practical Mini L-BOXX® with insert and separate compartment for the Swirl Finder SF 150-P LED light (not included).

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Swirl Finder Pocket Light

Order number 463.302



#### Technical attributes

|                  |                  |
|------------------|------------------|
| QTY/PKG          | 1                |
| Size (W x L x H) | 190 x 58 x 43 mm |
| Weight           | 0,056 kg         |

LED light for easy control of surface conditions. Due to the colour temperature and reproduction, surface damage such as holograms, scratches etc. become better visible. Light intensity 140 lumens and adjustable focus with a beam angle of 10° -70°, lighting time approx. 2 hours incl. batteries.

### Power 55 R

Order number 491.349



#### Technical attributes

|         |   |
|---------|---|
| QTY/PKG | 1 |
|---------|---|

Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Power 22 Q

Order number 491.357



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

#### Technical attributes

QTY/PKG

1