

## Metal-cutting band saw with swivelling saw frame

**SBG 4910**

Order number 390.518



### Metal-cutting band saw with swivelling saw frame

- + 2 belt speeds: for sawing solid and hollow sections
- + Recommended belt speeds: Step I: solid steel, stainless steel, aluminium; Step II: steel, stainless steel, aluminium tubes
- + Cutting without a stand: with 90° straight cut, round and square section, max. 80 mm, rectangular section max. 100 x 80 mm, freehand use 150 x 80 mm
- + Continuous tool-free adjustment of the cutting angle from 0° - 45°
- + With stand, easy release for freehand use
- + 3-point ball-bearing bandsaw blade guide for optimum blade control
- + With bracket locking device: for mobile applications and easy transport
- + Safety switch: prevents uncontrolled reactivation following power interruptions
- + Work without cooling fluids
- + Especially in fire hazardous surroundings the SBG for spark free cutting of metal

#### Technical attributes

Power input	850 watt
Power output	445 watt
Size of saw band	1335x13x0,65 mm
Belt speed	60 / 80 m/min
Max. cutting range: round cross sectional cut at 45°/90°	68 mm / 80 mm
Max. cutting range: square cross sectional cut at 45°/90°	60 mm / 80 mm
Max. cutting range: rectangular cross sectional cut at 45°/90°	68x55 mm / 100x80 mm
Cable length	4,0 m
Size (W x L x H)	640 x 310 x 390 mm
Weight of saw arm	7,9 kg
Weight (complete unit)	18,0 kg

#### Standard equipment

1 parallel guide fence	385.247
1 bimetal saw blade	1 piece