FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



RETECFLEX - the universal tool for renovation and modernization

RE 16-5 115, Kit E-Jet





RETECFLEX - the universal tool for renovation and modernization

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Motor: powerful, strong motor for quick working progress
- + Anti-Kickback this shuts down the motor on the tool being blocked
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Special gearbox: special gear ratio for high torque in the medium and low speed range
- + With steplessly adjustable, vibration-proof, ergonomic bail handle, for optimum handling and machine control
- + Dust-proof on/off switch
- + Effective dust extraction thanks to a large extraction cross-section. Simple, quick connection using the FLEX clip-system. No adapters or reducing sleeves are required
- + Extraction hood: with stepless height adjustment
- + Universal tool system can be adapted for a large number of renovation and modernisation applications. Compact, handy and ideal for working on small surfaces and on the edges of larger areas
- + Spindle lock
- + Grinding disc for abrasive materials. For removal of formwork transitions and concrete runs from freshly concreted surfaces, mineral adhesives, screeds, plaster, mortar, abrasive lime sand brick, sandstone, chamotte, asphalt.

Technical attributes	
Max. disc diameter	115 mm
Max. milling head Ø	80 mm
Scouring depth	0-6 mm
No load speed	1900-5500 rpm
Power input	1600 watt
Power output	950 watt
Tool fixture	Form fit
Cable length	4,0 m
Size (W x L x H)	355 x 160 x 67 mm
Weight	3,1 kg

Standard equipment	
1 Screed-Jet diamond grinding disc	503.061
1 extractor guard grinding Ø 115 mm with a brush ring	366.528
1 adjustable base scouring Ø 80 mm	366.897
1 velcro backing pad Bowl Ø 115/M14	503.754
Corundum sanding disc set Ø 115	1 set
1 bail handle	1 piece
1 ring hole spanner, SW 13	505.072
1 hexagon socket wrench, SW 4	102.229
3 fastening screws, M 8	3 pieces
1 carrying case L-BOXX [®] 238	414.093
1 case insert	414.182