FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



## Diamond stone cutter for wet cuts, mitre cuts up to 45°, with GFCI circuit breaker

## **CS 60 WET**

## Order number 374.016



## Diamond stone cutter for wet cuts, mitre cuts up to 45 $^{\circ}$ , with GFCI circuit breaker

- + High-performance motor: extra powerful for stone cutting and joint milling
- + Continuous cut depth setting from 0-60 mm, with rail guide up to 54 mm. In the mitre cut from 0-44 mm, with guide rail up to 38 mm
- + Continuous angle adjustment for mitre cuts from 0-45°
- + Cut marking at the base plate from  $0^{\circ}/30^{\circ}/45^{\circ}$  for rapid orientation
- + High-quality magnesium die-castings for protective cover and base plates
- + Motor protection made of rubber prevents the direct intake of spray water
- + Water supply: for an effective cooling of the diamond blade
- + Quick-fit brass coupling: for 1/2" water hose
- + GFCI operator protector circuit breaker: integrated in cord
- + Ideal for: Inserting water grooves in window sills or steps, work tops, facade slabs, terazzo slabs in garden design & landscaping, joint renovation in the floor
- + Spindle lock

Technical attributes	
Power input	1400 watt
Power output	840 watt
No load speed	6200 rpm
Diamond cutting disc Ø / arbor (inside Ø)	170 / 22,2 mm
Cutting depth / with guide rail	60 / 54 mm
Mitre cuttings	0-45 °
Depth of cut - mitre cut	5-44 mm
Depth of cut - mitre cut with guide rail	0-38 mm
Cable length	4,0 m
Size (W x L x H)	360 x 280 x 170 mm
Weight	4,5 kg

Standard equipment	
1 diamond cutting disc with segmented cutting edge	347.515
1 wrench for saw blade change	359.343
1 parallel guide fence	350.613
1 carrying case L-B0XX® 238	414.093
1 case insert	436.771