FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com




- . . . . . . . .

battery/head

## Cordless wall and ceiling sander Giraffe® with interchangeable head system 18.0 V

## GE MH 18.0-EC/5.0 Set+MH-X

## Order number 504.068



## Cordless wall and ceiling sander Giraffe® with interchangeable head system 18.0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Electronics: Speed preselection with adjustment wheel, overload protection, restart lock and temperature monitoring
- + Brushless motor with greater efficiency and a longer service life
- + Very handy, light-weight machine with optimum ease of operation. Provides comfortable and ergonomic working conditions
- + Fitted with innovative interchangeable head system. Sanding heads are attached and removed with a click
- + Excentric sanding head with a 4 mm stroke that makes it easy to achieve perfect surfaces in Q3 and Q4quality
- + Easy guiding: by optimal balance between motor and sanding head
- + Reliable force transmission and high flexibility thanks to the flexible drive shaft from. For decades established "FLEX technology". Thanks to this design principle the weight on the head of the Giraffe is reduced to a minimum. This facilitates handling.
- + Gimbal-mounted sanding head provides high flexibility and optimum adjustment for sanding walls and ceilings.
- + Effective dust extraction from between the brush ring and the sanding pad prevents clogging of the abrasive and promotes a dust-free working environment
- + Option of connecting the FLEX safety vacuum cleaners to the FLEX clip-system on the guide tube
- + Dust-proof on/off switch
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18,0 V battery packs

Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
No load speed	1150-1800 rpm
Orbit rate, no load (MH-T)	3950-6200 opm
Orbit rate, no load (MH-X)	3200-5000 opm
Sanding disc Ø	225 mm
Tool fixture	velcro
Tilt angle on the head	100 °
Length	1440 mm
Weight excluding	2,8 ka

457.205
406.023
445.894
417.882
408.867